

~STKM 機械構造用炭素鋼鋼管~

外径 (mm)	厚さ (mm)	単重 (kg/m)
6	1.0	0.123
8	1.0	0.173
9.5	1.0	0.21
10	1.0	0.222
	1.2	0.26
	1.6	0.331
13	1.0	0.296
12.7	1.0	0.289
	1.2	0.34
	1.6	0.438
	2.0	0.528
13.8	1.2	0.373
	1.6	0.481
	2.0	0.582
	2.3	0.652
14	1.0	0.321
15.9	1.0	0.367
	1.2	0.435
	1.6	0.564
	2.0	0.686
	2.3	0.771
16	1.0	0.37
17.3	1.0	0.402
	1.6	0.619
	2.3	0.851
18	1.6	0.647
	2.0	0.789
	2.3	0.89
19.1	1.2	0.53
	1.6	0.69
	2.0	0.843
	2.3	0.953
22.2	1.0	0.523
	1.2	0.621
	1.4	0.718
	1.6	0.813

外径 (mm)	厚さ (mm)	単重 (kg/m)
22.2	2.0	0.996
	2.3	1.13
25.4	1.0	0.602
	1.2	0.716
	1.4	0.829
	1.6	0.939
	2.0	1.15
27.2	2.3	1.31
	2.3	1.41
	3.2	1.89
28.6	1.2	0.811
	1.4	0.939
	1.6	1.07
	2.0	1.31
	2.3	1.49
31.8	1.2	0.906
	1.6	1.19
	2.0	1.47
	2.3	1.67
	3.2	2.26
34	1.6	1.28
	2.3	1.8
35	1.6	1.32
38.1	1.2	1.09
	1.6	1.44
	2.0	1.78
42.7	1.2	1.23
	1.6	1.62
48.6	1.6	1.85
50.8	1.6	1.94
	2.0	2.41
	2.3	2.75
60.5	1.6	2.32
	2.0	2.89
76.3	1.6	2.95

~STKMR 機械構造用角形鋼管~(正方形)

外径 (mm)	厚さ (mm)	単重 (kg/m)
9 x 9	1.0	0.289
13 x 13	1.2	0.53
	1.6	0.69
16 x 16	1.2	0.621
	1.6	0.813
19 x 19	1.2	0.716
	1.6	0.939
21 x 21	1.2	0.811
	1.6	1.07
22 x 22	1.2	0.811
	1.6	1.07
24 x 24	1.2	0.906
	1.6	1.19
25 x 25 (角出し)	1.2	0.971
	1.6	1.28
	2.0	1.58
25 x 25 (R付き)	1.2	0.906
	1.6	1.19
26 x 26	1.0	0.76
	1.2	0.906
28 x 28	1.2	1.09
	1.6	1.44
30 x 30	2.3	2.03
31 x 31	1.2	1.09
	1.6	1.44
32 x 32	1.2	1.23
	1.6	1.62
38 x 38	1.6	1.94
40 x 40	1.6	1.94
	2.3	2.75
	3.2	3.76
45 x 45	1.6	2.32
60 x 60	1.6	2.95

~STKM-H ハイテンション鋼管~

外径 (mm)	厚さ (mm)	単重 (kg/m)
12.7	1.4	0.39
	1.6	0.438
13	1.4	0.4
	1.6	0.45
19.1	1.2	0.53
	1.6	0.69
	2.0	0.843
22.2	1.4	0.718
	1.6	0.813
	1.8	0.906
25.4	1.4	0.829
38.1	1.6	1.44

~溶融亜鉛めっき鋼管~

外径 (mm)	厚さ (mm)	単重 (kg/m)
19.1	1.2	0.53
28.6	1.2	0.811
35	1.6	1.32
38.1	1.2	1.09
42.7	1.4	1.43
48.6	1.4	1.63
57.2	1.4	1.93
	2.1	2.85
	2.3	3.11
60.5	3.2	4.52

～STKMR 機械構造用角形鋼管～(長方形)

外径 (mm)	厚さ (mm)	単重 (kg/m)
19 x 10	1.2	0.53
22 x 10	1.2	0.621
24 x 14	1.2	0.716
	1.6	0.939
25 x 12	1.2	0.716
	1.6	0.939
28 x 18	1.2	0.906
30 x 20	1.2	0.906
	1.6	1.19
32 x 14	1.2	0.906
	1.6	1.19
32 x 16	1.2	0.906
	1.6	1.19
40 x 16	1.2	1.09
	1.6	1.44
40 x 18	1.2	1.09
	1.6	1.44
40 x 20	1.2	1.09
	1.6	1.44
	2.3	2.03
40 x 25	1.2	1.23
	1.6	1.62
50 x 16	1.6	1.62
	2.0	2.01
50 x 20	1.2	1.23
	1.6	1.62
	2.0	2.12
	2.3	2.25
50 x 25	2.0	2.3
50 x 26	1.4	1.71
	1.6	1.94
50 x 30	1.6	1.94
	2.3	2.75
60 x 30	1.2	1.75
	1.6	2.33

外径 (mm)	厚さ (mm)	単重 (kg/m)
70 x 25	1.4	2.14
	1.6	2.44
70 x 30	1.6	2.44
75 x 25	1.6	2.44
80 x 40	1.6	2.95
90 x 30	2.3	4.2

～平行楕円パイプ～

外径 (mm)	厚さ (mm)	単重 (kg/m)
23 x 12	1.2	0.53
25 x 12	1.2	0.586
	2.0	0.937
25.5 x 15.5	1.6	0.813
30 x 15	2.0	1.15
30.5 x 15.5	1.6	0.939
37 x 14	1.2	0.811
	2.0	1.31
	2.3	1.49
40 x 20	1.6	1.19
46 x 20	1.6	1.44
49 x 25	1.6	1.62
54 x 28	1.2	1.3
	1.6	1.71
	2.0	2.12
58.5 x 30	2.3	2.63
68 x 20	1.6	1.94
76.5 x 32	1.6	2.32
80 x 25	1.6	2.32

～STK 一般構造用炭素鋼鋼管～

外径 (mm)	厚さ (mm)	単重 (kg/m)
21.7	1.9	0.928
27.2	1.9	1.19
	2.3	1.41
34	2.3	1.8
42.7	2.3	2.29
48.6	2.3	2.63
	3.2	3.58
60.5	2.3	3.3
	2.8	3.98
	3.2	4.52
76.3	2.3	4.2
	2.8	5.08
	3.2	5.77

～SGP 配管用炭素鋼鋼管～

外径 (mm)	厚さ (mm)	単重 (kg/m)
6A	10.5	2.0
10A	17.3	2.3
15A	21.7	2.8
20A	27.2	2.8
25A	34	3.2
32A	42.7	3.5
40A	48.6	3.5

※在庫サイズは常に変更の可能性があります。

上記表は参考程度にご活用ください。

※材料長、単価等は都度お問合せください。

※上記以外の品目でも、お取り寄せなど

対応が可能なものもございます。

お気軽にお申し付けください。

～STKR 一般構造用角形鋼管～

外径 (mm)	厚さ (mm)	単重 (kg/m)
50 x 50	1.6	2.38
	2.3	3.34
	3.2	4.5
60 x 60	1.6	2.88
	2.3	4.06
	3.2	5.5
75 x 75	2.3	5.14
	3.2	7.01
100 x 100	2.3	6.95
	3.2	9.52
	4.5	13.1
60 x 30	1.6	2.13
	2.3	2.98
	3.2	3.99
75 x 45	2.3	4.06
100 x 50	2.3	5.14
	3.2	7.01