

# ～STKM 機械構造用炭素鋼鋼管～

外径 (mm)	厚さ (mm)	単重 (kg/m)
6	1.0	0.123
8	1.0	0.173
9.5	1.0	0.21
10	1.0	0.222
	1.2	0.26
	1.6	0.331
13	1.0	0.296
12.7	1.0	0.289
	1.2	0.34
	1.6	0.438
	2.0	0.528
13.8	1.2	0.373
	1.6	0.481
	2.0	0.582
	2.3	0.652
14	1.0	0.321
15.9	1.0	0.367
	1.2	0.435
	1.6	0.564
	2.0	0.686
	2.3	0.771
16	1.0	0.37
17.3	1.0	0.402
	1.6	0.619
	2.3	0.851
18	1.6	0.647
	2.0	0.789
	2.3	0.89
19.1	1.2	0.53
	1.6	0.69
	2.0	0.843
	2.3	0.953
22.2	1.0	0.523
	1.2	0.621
	1.4	0.718
	1.6	0.813

外径 (mm)	厚さ (mm)	単重 (kg/m)
22.2	2.0	0.996
	2.3	1.13
25.4	1.0	0.602
	1.2	0.716
	1.4	0.829
	1.6	0.939
	2.0	1.15
27.2	2.3	1.31
	2.3	1.41
	3.2	1.89
28.6	1.2	0.811
	1.4	0.939
	1.6	1.07
	2.0	1.31
	2.3	1.49
31.8	1.2	0.906
	1.6	1.19
	2.0	1.47
	2.3	1.67
34	3.2	2.26
	1.6	1.28
35	2.3	1.8
	1.6	1.32
38.1	1.2	1.09
	1.6	1.44
	2.0	1.78
42.7	1.2	1.23
	1.6	1.62
48.6	1.6	1.85
50.8	1.6	1.94
	2.0	2.41
	2.3	2.75
60.5	1.6	2.32
	2.0	2.89
76.3	1.6	2.95