

～STKMR 機械構造用角形鋼管～(正方形)

外径 (mm)	厚さ (mm)	単重 (kg/m)
9 x 9	1.0	0.289
13 x 13	1.2	0.53
	1.6	0.69
16 x 16	1.2	0.621
	1.6	0.813
19 x 19	1.2	0.716
	1.6	0.939
21 x 21	1.2	0.811
	1.6	1.07
22 x 22	1.2	0.811
	1.6	1.07
24 x 24	1.2	0.906
	1.6	1.19
25 x 25 (角出し)	1.2	0.971
	1.6	1.28
	2.0	1.58
25 x 25 (R付き)	1.2	0.906
	1.6	1.19
26 x 26	1.0	0.76
	1.2	0.906
28 x 28	1.2	1.09
	1.6	1.44
30 x 30	2.3	2.03
31 x 31	1.2	1.09
	1.6	1.44
32 x 32	1.2	1.23
	1.6	1.62
38 x 38	1.6	1.94
40 x 40	1.6	1.94
	2.3	2.75
	3.2	3.76
45 x 45	1.6	2.32
60 x 60	1.6	2.95

～STKM-H ハイテンション鋼管～

外径 (mm)	厚さ (mm)	単重 (kg/m)
12.7	1.4	0.39
	1.6	0.438
13	1.4	0.4
	1.6	0.45
19.1	1.2	0.53
	1.6	0.69
	2.0	0.843
22.2	1.4	0.718
	1.6	0.813
	1.8	0.906
25.4	1.4	0.829
38.1	1.6	1.44

～溶融亜鉛めっき鋼管～

外径 (mm)	厚さ (mm)	単重 (kg/m)
19.1	1.2	0.53
28.6	1.2	0.811
35	1.6	1.32
38.1	1.2	1.09
42.7	1.4	1.43
48.6	1.4	1.63
57.2	1.4	1.93
	2.1	2.85
	2.3	3.11
60.5	3.2	4.52